

Infrared Data Association

Guidelines for *Ultra* Protocols



Version 1.0

October 15, 1997

California Wireless, Inc.
Ericsson
Matsushita/Panasonic
Motorola
NEC
Nokia Mobile Phones, Ltd.
NTT DoCoMo
Puma

Authors:

Petri Nykänen Petri.Nykanen@nmp.nokia.com (Nokia Mobile Phones Ltd.)

Paul Rubin phr@wireless.com, Mike Cheponis mike@wireless.com (California Wireless, Inc.)

Contributors:

David W. Suvak (Counterpoint Systems Foundry)

Mark Hansen, Robert K. Lockhart (Motorola)

Document Status: Version 1.0

INFRARED DATA ASSOCIATION (IrDA) - NOTICE TO THE TRADE -**SUMMARY:**

Following is the notice of conditions and understandings upon which this document is made available to members and non-members of the Infrared Data Association.

- Availability of Publications, Updates and Notices
- Full Copyright Claims Must be Honored
- Controlled Distribution Privileges for IrDA Members Only
- Trademarks of IrDA - Prohibitions and Authorized Use
- No Representation of Third Party Rights
- Limitation of Liability
- Disclaimer of Warranty
- Certification of Products Requires Specific Authorization from IrDA after Product Testing for IrDA Specification Conformance

IrDA PUBLICATIONS and UPDATES:

IrDA publications, including notifications, updates, and revisions, are accessed electronically by IrDA members in good standing during the course of each year as a benefit of annual IrDA membership. Electronic copies are available to the public on the IrDA web site located at irda.org. IrDA publications are available to non-IrDA members for a pre-paid fee. Requests for publications, membership applications or more information should be addressed to: Infrared Data Association, P.O. Box 3883, Walnut Creek, California, U.S.A. 94598; or e-mail address: info@irda.org; or by calling John LaRoche at (510) 943-6546 or faxing requests to (510) 934-5600.

COPYRIGHT:

1. Prohibitions: IrDA claims copyright in all IrDA publications. Any unauthorized reproduction, distribution, display or modification, in whole or in part, is strictly prohibited.
2. Authorized Use: Any authorized use of IrDA publications (in whole or in part) is under NONEXCLUSIVE USE LICENSE ONLY. No rights to sublicense, assign or transfer the license are granted and any attempt to do so is void.

DISTRIBUTION PRIVILEGES for IrDA MEMBERS ONLY:

IrDA Members Limited Reproduction and Distribution Privilege: A limited privilege of reproduction and distribution of IrDA copyrighted publications is granted to IrDA members in good standing and for sole purpose of reasonable reproduction and distribution to non-IrDA members who are engaged by contract with an IrDA member for the development of IrDA certified products. Reproduction and distribution by the non-IrDA member is strictly prohibited.

TRANSACTION NOTICE to IrDA MEMBERS ONLY:

Each and every copy made for distribution under the limited reproduction and distribution privilege shall be conspicuously marked with the name of the IrDA member and the name of the receiving party. Upon reproduction for distribution, the distributing IrDA member shall promptly notify IrDA (in writing or by e-mail) of the identity of the receiving party.

A failure to comply with the notification requirement to IrDA shall render the reproduction and distribution unauthorized and IrDA may take appropriate action to enforce its copyright, including but not limited to, the termination of the limited reproduction and distribution privilege and IrDA membership of the non-complying member.

TRADEMARKS:

1. Prohibitions: IrDA claims exclusive rights in its trade names, trademarks, service marks, collective membership marks and certification marks (hereinafter collectively "trademarks"), including but not limited to the following trademarks: INFRARED DATA ASSOCIATION (wordmark alone and with IR logo), IrDA (acronym mark alone and with IR logo), IR logo, IR DATA CERTIFIED (composite mark), and MEMBER IrDA (wordmark alone and with IR logo). Any unauthorized use of IrDA trademarks is strictly prohibited.

2. Authorized Use: Any authorized use of a IrDA collective membership mark or certification mark is by NONEXCLUSIVE USE LICENSE ONLY. No rights to sublicense, assign or transfer the license are granted and any attempt to do so is void.

NO REPRESENTATION of THIRD PARTY RIGHTS:

IrDA makes no representation or warranty whatsoever with regard to IrDA member or third party ownership, licensing or infringement/non-infringement of intellectual property rights. Each recipient of IrDA publications, whether or not an IrDA member, should seek the independent advice of legal counsel with regard to any possible violation of third party rights arising out of the use, attempted use, reproduction, distribution or public display of IrDA publications.

IrDA assumes no obligation or responsibility whatsoever to advise its members or non-members who receive or are about to receive IrDA publications of the chance of infringement or violation of any right of an IrDA member or third party arising out of the use, attempted use, reproduction, distribution or display of IrDA publications.

LIMITATION of LIABILITY:

BY ANY ACTUAL OR ATTEMPTED USE, REPRODUCTION, DISTRIBUTION OR PUBLIC DISPLAY OF ANY IrDA PUBLICATION, ANY PARTICIPANT IN SUCH REAL OR ATTEMPTED ACTS, WHETHER OR NOT A MEMBER OF IrDA, AGREES TO ASSUME ANY AND ALL RISK ASSOCIATED WITH SUCH ACTS, INCLUDING BUT NOT LIMITED TO LOST PROFITS, LOST SAVINGS, OR OTHER CONSEQUENTIAL, SPECIAL, INCIDENTAL OR PUNITIVE DAMAGES. IrDA SHALL HAVE NO LIABILITY WHATSOEVER FOR SUCH ACTS NOR FOR THE CONTENT, ACCURACY OR LEVEL OF ISSUE OF AN IrDA PUBLICATION.

DISCLAIMER of WARRANTY:

All IrDA publications are provided "AS IS" and without warranty of any kind. IrDA (and each of its members, wholly and collectively, hereinafter "IrDA") EXPRESSLY DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE AND WARRANTY OF NON-INFRINGEMENT OF INTELLECTUAL PROPERTY RIGHTS.

IrDA DOES NOT WARRANT THAT ITS PUBLICATIONS WILL MEET YOUR REQUIREMENTS OR THAT ANY USE OF A PUBLICATION WILL BE UN-INTERRUPTED OR ERROR FREE, OR THAT DEFECTS WILL BE CORRECTED. FURTHERMORE, IrDA DOES NOT WARRANT OR MAKE ANY REPRESENTATIONS REGARDING USE OR THE RESULTS OR THE USE OF IrDA PUBLICATIONS IN TERMS OF THEIR CORRECTNESS, ACCURACY, RELIABILITY, OR OTHERWISE. NO ORAL OR WRITTEN PUBLICATION OR ADVICE OF A REPRESENTATIVE (OR MEMBER) OF IrDA SHALL CREATE A WARRANTY OR IN ANY WAY INCREASE THE SCOPE OF THIS WARRANTY.

LIMITED MEDIA WARRANTY:

IrDA warrants ONLY the media upon which any publication is recorded to be free from defects in materials and workmanship under normal use for a period of ninety (90) days from the date of distribution as evidenced by the distribution records of IrDA. IrDA's entire liability and recipient's exclusive remedy will be replacement of the media not meeting this limited warranty and which is returned to IrDA. IrDA shall have no responsibility to replace media damaged by accident, abuse or misapplication. ANY IMPLIED WARRANTIES ON THE MEDIA, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, ARE LIMITED IN DURATION TO NINETY (90) DAYS FROM THE DATE OF DELIVERY. THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS, AND YOU MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM PLACE TO PLACE.

CERTIFICATION and GENERAL:

Membership in IrDA or use of IrDA publications does NOT constitute IrDA compliance. It is the sole responsibility of each manufacturer, whether or not an IrDA member, to obtain product compliance in accordance with IrDA rules for compliance. All rights, prohibitions of right, agreements and terms and conditions regarding use of IrDA publications and IrDA rules for compliance of products are governed by the laws and regulations of the United States. However, each manufacturer is solely responsible for compliance with the import/export laws of the countries in which they conduct business. The information contained in this document is provided as is and is subject to change without notice.

TABLE OF CONTENTS

1. INTRODUCTION	1
1.1 Purpose	1
1.2 Scope	1
1.3 References	1
2. MINIMUM CAPABILITIES	2
2.1 Framing	2
2.2 Media Access Control Procedures	3
2.2.1 Unidirectional Devices	3
2.2.2 Bi-directional Devices	4
3. OPTIONAL CAPABILITIES	5
3.1 Optional operation to support 2400 BPS-only stations	5
3.2 Segmentation and Re-assembly (SAR)	5

1. Introduction

1.1 Purpose

The purpose of this document is to present the rules that apply any *Ultra* protocols that utilize IrDA data link layer framing. *Ultra* protocols in the context of this document refer to all protocols implemented on top of the connectionless data service of the IrLAP specification.

1.2 Scope

This document is intended to be a companion document to the IrDA IrLAP, IrLMP, and OBEX specifications (see section 1.3 References). For most part the aforementioned specifications provide the complete description of the respective protocols. Where exceptions are made, they are clearly marked with **Exception** text next to the exception. Reader should be familiar with the aspects of the connectionless data service described in IrLAP and IrLMP specifications.

1.3 References

IRDALAP	Serial Infrared Link Access Protocol, IrLAP, Version 1.1, Infrared Data Association
IRDALMP	Link Management Protocol, IrLMP, Version 1.1, Infrared Data Association
IRDAOBEX	IrDA Object Exchange Protocol, IrOBEX, Version 1.0, Infrared Data Association

2. Minimum Capabilities

This section describes the minimum IrLAP and IrLMP capabilities that are required in every device that supports *Ultra*. Every station that supports receiving and/or transmitting *Ultra* frames shall implement the IrLAP framing as specified in the IrLAP specification. Every station shall follow the IrLAP Media Access Control (MAC) rules. The following sections further explain the requirements.

Ultra devices are not required to support device discovery, sniffing, or connection-oriented services. All communication takes place on 9600 BPS, with optional support for 2400 BPS. *Ultra* protocol alone does not support reliable data service, nor does it support device selection based on addressing.

Nothing prevents the data packets from including additional information that is interpreted by the set of cooperating devices as address information.

Higher level software can be layered on top of *Ultra* to achieve reliable data transport, on a frame-by-frame basis, or, indeed, file transfer.

2.1 Framing

The IrDA-SIR framing requirements described in IrLAP 1.1 specification, appendix D (IrLAP Frame Wrappers) apply to all *Ultra* protocols. In Figure 1 is shown the framing, and the IrLAP and IrLMP layer specific headers.




Figure 1. The framing and headers

This Figure shows three levels of definition for the connectionless UI frames. Level 1 headers are defined in the IrLAP specification, level 2 headers are defined in IrLMP, and this document defines the headers specific to level 3.

When the connectionless UI frames are utilized, the following restrictions apply:

The service data payload is required to start with a protocol identifier octet (PID). This octet is used to indicate what protocol is used in the payload. The eighth bit of the PID octet is an extension bit and indicates whether or not an additional PID octet follows. PID information must always be presented with minimum possible number of PID octets. See Table 1 for the PID bit definitions. The definition of the extension capability follows closely the extension capability defined in section 3.4.1.1 Service Hints of IrLMP.

For more information on the requirements for connectionless UI frames, please refer to section 3.2.2 Receive Demultiplexer in IrLMP specification, cases (f), and (g). Note, that the Poll bit is required to be set in all connectionless UI frames.

The service data field including the protocol identifier(s), prior to transparency byte-stuffing, shall not exceed 382 octets in length.

It is highly recommended that the service data field including the protocol identifier(s), prior to transparency byte-stuffing, shall be limited to 62 octets in length. Resource restrained systems may not be able to send or to receive frames that exceed this value.

Table 1. The PID Octet Encoding

PID Octet	
Bit	Function
0	Protocol ID bit 0
1	Protocol ID bit 1
2	Protocol ID bit 2
3	Protocol ID bit 3
4	Protocol ID bit 4
5	Protocol ID bit 5
6	Protocol ID bit 6
7	Extension

All PID values are reserved and assigned by IrDA.

Protocol Identifier: 0x01 - Ultra OBEX

The service data payload following the Ultra OBEX protocol identifier shall follow the conventions set forth in the IrDA OBEX specification for utilization of OBEX in *Ultra* protocols. This means that only PUT and GET primitives defined in the OBEX specification may be placed in the service data field when the protocol identifier has a value of 01h. Furthermore, Ultra OBEX utilizes SAR functionality, which is implemented by placing SAR header in front of the OBEX command primitive. Refer to section 3.2. Segmentation and Re-assembly (SAR) for more information on the SAR functionality.

The Ultra OBEX frame structure is shown in Figure 2.




Figure 2. Ultra OBEX frame structure

2.2 Media Access Control Procedures

The MAC procedures described in IrLAP 1.1 specification, section 6.13 generally apply to all *Ultra* protocols.

2.2.1 Unidirectional Devices

No exceptions.

2.2.2 Bi-directional Devices

Exception: When any *Ultra* protocol provides device selection capability to ensure that only one station will try to reply to initiated requests, the replying station may generate a frame reply to incoming frame without media sense period, provided that it initiated the reply before 500 ms passes.

In other words, when it is clear that the request is directed to the local station, the local station may initiate reply as soon as possible. If 500 ms passes before the reply is initiated, then a media sense period is required. Care should be taken to always use the number of XBOFs required in the IrLAP specification when sending the reply frames, or problems with minimum turn-around time are inevitable.

3. Optional Capabilities

This section describes the optional capabilities that can be utilized by *Ultra* protocols.

3.1 Optional operation to support 2400 BPS-only stations

Devices supporting *Ultra* protocols may be implemented in such a way that they support operation only on 2400 BPS, and not on 9600 BPS as the IrLAP specification states. Refer to IrLAP specification, appendix A (2400 BPS devices) for full list of requirements. The following additional requirements apply:

The IrLMP frame payload data field, prior to transparency byte-stuffing, shall not exceed 92 octets in length.

The Service data field, prior to transparency byte-stuffing, shall not exceed 90 octets in length.

3.2 Segmentation and Re-assembly (SAR)

The SAR functionality means the capability to segmentate transmitted data to several smaller frames, and on the receiving side to re-assemble the received data back to the original size. This functionality may be implemented for an *Ultra* service in order to enable devices that can handle only minimum size frames while still being capable of sending/receiving larger information content.

All MAC rules apply to devices implementing SAR. This means that after each data fragment, the device must initiate a new 500+ ms media sense period. If the medium is free after the media sense period, then sending of the rest of the fragments can continue.

The SAR functionality specified here does not contain transaction id or any similar facility. It is prone to errors if used for extensive data exchange. Errors can happen for example in a situation where two messages contain the same amount of fragments, and the end first message is lost and the start of the second message is lost, while messages are being sent back-to-back.

The receiving station does not have any facility to indicate back to the sending station that a fragment was not received. Thus this SAR facility is only applicable to situations in which information is offered by one station to another unidirectionally. Receiving station is always required to discard all the fragments it receives if any of the fragments belonging to the message is lost, or any fragment is received out of sequence.

If no fragments of a message are received for 2 seconds while the current index is not equal to the final index, the receiving station is allowed to discard all the fragments. In practice this means that if the transmission medium is lost while sending a long sequence, then the sending must be started again.

In Figure 3 is shown an example in which three frames are sent using the SAR facility, while following the MAC procedures set forth in the IrLAP 1.1 specification.



Figure 3. SAR and MAC timing

Table 2. The PID Octet Encoding

SAR Octet	
Bit	Function
0	Bit 0 of current segment index
1	Bit 1 of current segment index
2	Bit 2 of current segment index
3	Bit 3 of current segment index
4	Bit 0 of final segment index
5	Bit 1 of final segment index
6	Bit 2 of final segment index
7	Bit 3 of final segment index

The segment index may be any value from 0 to 14 decimal. Value 15 is reserved. The final segment index may be any value from 0 to 14. Value 15 is reserved.

When SAR is defined to be a part of the payload for a service but the functionality is not needed, then this can be indicated by setting both current segment index and the final segment index to 0, i.e., only one segment in the sequence.